



**american**<sup>™</sup>  
**lime technology**  
sustainable building innovation

Details are INDICATIVE ONLY and need to be made project specific.

While reasonable care has been taken to ensure that the information included in this drawing was accurate at the time of issue, we reserve the right to change specifications at any time. Final detailing remains the responsibility of the designer due to site & client specific requirements.

Do not scale from this drawing.

Drawing to be read in conjunction with all standard series drawings

*Rafter depths to architect's specification.*

Warm roof design and roof finish to the designer's specification

Eaves detail to the designer's specification

1000mm Wide Alkali Resistant Mesh Centered Along Intersecting Walls and Floors

*All structural fasteners to be non-ferrous, any galvanized fasteners to be painted with red oxide primer or bitumen paint.*

Depth of Tradical® Hemcrete® to suit thermal performance required

5/8" Baumit FL68 lime render directly on to Tradical® Hemcrete®

External Finish:  
1/8" Pre-colored Baumit SEP Lime Render Top Coat

Scrim cloth or mesh to corner junction of wall and ceiling

3/8" U.S. Heritage Group HS-B hydraulic lime plaster base coat

Internal Finish Options:  
1/8" U.S. Heritage Group HS-F Hydraulic Lime Stucco/Plaster Finish Coat with 3 coats limewash or tint plaster to final finish color

Wood frame and bracing requirements to architect's specification

EXTERIOR

INTERIOR



12.11	US Conversion	UK File Name	DWN	CKD	<b>Standard Warm Roof Section</b> Baumit Render on Tradical® Hemcrete® Internal Wood Frame
	ALTJTradHem]Render]STD_WRM_ROOF	1_10_A4_LMT_3			
			JK	DW	